THE WHISTLER GROUP, INC.
CORPORATE HEADQUARTERS
13016 N. Walton Blvd.
Bentonville, AR 72712

TEL (479) 273-6012 FX (479) 273-2927

#### **CUSTOMER RETURN CENTER**

1201 N. Dixieland Rd. Rogers, AR 72756 Consumer Relations Tel (800) 531-0004 Email: info@whistlergroup.com

P/N 202880, © WHISTLER 2003

www.whistlergroup.com

# OWNER'S MANUAL 3300A/3400 LASER/RADAR DETECTOR



www.whistlergroup.com

If you have questions concerning the operation of this Whistler product please call:

# **CUSTOMER SERVICE** 1-800-531-0004

Monday - Friday • 8:00 am - 5:00 pm CT or visit our website www.whistlergroup.com

Please keep the receipt in a safe place. You may register your product online at www.whistlergroup.com. For warranty verification purposes, a copy of your dated store receipt must still accompany any unit sent in for warranty work. If the unit is returned without a dated store receipt an out of warranty service charge applies.

Note: Your warranty period begins at the time of purchase. The warranty is validated only by the dated store receipt! Now is the time to record the serial number of the unit in the space provided in the warranty section of the manual.

#### INTRODUCTION

Dear Whistler Owner,

For many of us, a vehicle is more than just transportation. It can be a mobile office, communications or entertainment center, or simply an expression of our personality. Whistler products are designed to make the time you spend in your vehicle more productive, more fulfilling, safer, or just simply more fun. Our mission is to provide products that improve your driving experience.

Your new Whistler 3300A/3400 laser/radar detector detects all radar, laser and safety radar systems, plus offers Whistler's exclusive Safe Driving System™ keeping you informed of road hazards and adverse weather. Plus, Whistler's unique Stay Alert™ feature tests driver's alertness on long solo trips. Whistler's 3300A/3400 also offers a digital display with safety messages to keep you informed while you drive.

To fully acquaint yourself with the operation of the Whistler 3300A/3400 and to better understand the differences between detecting radar, laser and safety radar signals, we recommend reading this entire manual.

Enjoy the Whistler 3300A/3400 and please drive safely.

Sincerely,

THE WHISTLER GROUP

## TABLE OF CONTENTS

TopicPageModel Features Summary3 - 4	
Operation	
Communication Breakdown	
Are Detectors Legal?	
Speed Monitoring Technologies	
Accessories20 - 29	

#### WHISTLER FEATURES

#### Whistler 3300A / 3400



Whistler's ergonomic and user-friendly design provides a new level of operating convenience. Special features include:

- **Speaker –** Provides distinct audio warnings for X, K, Ka band radar, safety radar, laser and VG-2.
- Radar Antenna Compact, high-efficiency antenna receive radar signals.
- Laser Antenna High gain optical lens provides increased sensitivity and field of view for leading-edge laser detection front and rear.


#### WHISTLER FEATURES

- City/City 1/City 2 Mode Reduces the annoyance of false alerts typically encountered in urban driving areas.
- Quiet/Menu Button Pressing QUIET before a signal is detected engages Auto Quiet Mode which automatically reduces the audio level after the initial warning to a low audio level setting. Pressing QUIET during a radar/laser encounter silences audio alerts, while allowing visual alerts to keep you informed. Pressing and holding for 2 seconds allows you to enter Option Select Mode (see page 12).
- Power/Volume Control Turns unit on/off and adjusts audio level.
- High Visibility Display Provides distinct visual confirmation of signals detected, signal strength, and indicates engaged modes of operation.
- Dim/Dark Mode- Reduces the illumination of the display.

#### Power On And Self-Test

Each time your Whistler detector is turned on, an automatic self-test sequence confirms that the speaker and visual displays are functional.

• Press **P/V** or apply Power. Display reads:



#### Memory/Beep Confirmation

All features selected (except Stay Alert and Quiet) are retained in memory. Each time a button is pressed one beep confirms feature "on", two beeps confirm feature "off".

#### Audio Level Adjustment

The audio levels can be adjusted high to low, or low to high, in four steps: (1) is no audio level, (4) the highest.

- Press and hold P/V to increase audio level.
- Press and hold P/V to decrease audio level.


As audio level is adjusted, beeps are provided and the display indicates volume level. Example:



#### Auto Quiet Mode

Auto Quiet reduces the selected audio level to level (1) approximately 5 seconds after a radar or safety radar signal is detected. The alert for any new signal within 20 seconds will resume at level (1). Auto Quiet does not affect VG-2 or laser alerts.

• Press Quiet (before a signal is detected) to engage Auto Quiet. Display reads:



- Once the Auto Quiet mode is engaged, you may cancel the audio alarm by pressing **Quiet**.
- Press Quiet (when the unit is not alarming) to cancel Auto Quiet mode.

**Note:** When Auto Quiet engages, it cancels the audio to the optional Voice Module.


#### Quiet Mode

Quiet Mode cancels the audio during an alert and any new alert within 20 seconds. After 20 seconds, approximately 2 beeps are provided on any new alert and unit then remains quiet.


- Press Quiet to cancel the audio.
- Press **Quiet** a second time during an alert to restore the standard audio alert pattern; or turn the unit off, then on.

#### Temperature/Voltage Mode

The unit can be programmed to display either the outside temperature or battery voltage along with Highway/City modes. See Option Select Mode. Display reads:



• Ice Warning Mode: When temperature drops to 32°F display reads:



Unit then gives a unique warning tone. This will only happen once after the unit is first turned on. When either Hi T or Lo T is displayed the limits of the temperature sensor have been reached.

**Note:** Temperature may rise while vehicle is stopped and idling, this is normal.


#### Engaging/Disengaging VG-2

See option select mode to turn this feature on.


#### City/City 1/City 2 Mode

Whistler's Three Stage City Mode is designed to reduce the annoyance of automatic door openers, intrusion alarms and other devices which share frequencies with police radar.


• Press City to engage City. Display reads:




• Pressing City a second time engages City 1. Display reads:



• Pressing City a third time engages City 2. Display reads:



 Pressing City a fourth time cancels City, City 1, and City 2. Display reads:



In City Mode, weak speed/safety radar signals give an initial alarm of two beeps, and then remains quiet unless the signal becomes very strong. When the signal strength increases, two additional beeps are provided. In City 1 Mode, only the X band sensitivity is lowered. In City 2 Mode, X-band is not detected. **CAUTION:** When selecting this mode, some towns/small cities may still be using X band radar.

If Auto Quiet is engaged in City 1 or City 2 modes and the unit receives a strong radar signal, the unit performs the Auto Quiet feature. City Modes do not change the audio alert for laser or VG-2.

#### Dim/Dark/Temperature/Voltage Modes

Dim/Dark Mode reduces the illumination of the display.

• Press **Dark** to reduce illumination to a Dim setting. Display reads:



 Pressing Dark a second time engages Dark Mode. Display reads:



Dim or dark can be engaged during an alert. In Dark Mode, the display goes dark for as long as a signal is being detected and for 20 seconds after, then the display returns to the dimmer setting.


• Pressing **Dark** a third time restores full illumination to the display.

The Dark Button will allow the display to momentarily switch to the outside temperature reading.

• Press and hold Dark for 2 seconds until unit beeps once then release. Display switches:



If Temperature or Battery Voltage is programmed (see Option Select Mode), pressing and holding Dark for 2 seconds will momentarily switch to the other reading. Example:



#### Stay Alert™ Feature

The Stay Alert™ Feature is designed to test a driver's alertness. To engage (when unit is not alarming):

• Press and hold City for 2 seconds. Display reads:

Within 30-60 seconds two beeps are sounded; to show alertness, the driver must press either the Dark, City or Quiet button within 3-5 seconds. If the button is pressed within 3-5 seconds, the cycle is repeated.

If a button was not pressed within 3-5 seconds alarm sounds and the display reads:



Press P/V to exit.

WARNING!!! Stay Alert™ is NOT intended as a substitute for adequate rest. You should NOT operate a vehicle if you are drowsy. During extended periods of vehicle operation, you should take frequent breaks. Improper reliance on the Stay Alert™ feature may result in vehicle damage, personal injury or death. NEVER OPERATE A VEHICLE IF YOU ARE DROWSY.

#### Integrated Real Voice®

When selected and Optional Voice Module is connected, Real Voice® will be used to articulate the following:

- 1. Band Identification
- 2. Safety Warning System<sup>™</sup> messages

**NOTE:** In certain cases the voice message does not replicate the text message.

3. Feature Selection 1

#### Option Select Mode

Entering Option Select Mode allows you to customize options such as Tone Select, Real Voice®, Abbreviated Power Up Sequence test and VG-2 Mode. When selecting options, Dark (D)=yes, City (C)=no, Quite (Q)=next selection. Any one of these must be pressed within 20 seconds or options mode will automatically be exited. To enter:

Press Q:	*Display Reads:	To Change,	Option: Reads:	
For 2 Seconds	CUSTOM	D or C	Custom Mode Night Mode Truck Mode	
2nd time	TEMP 'F	D = °F C = °C	Changes Temp Reading	
3rd time	TONE 3	D or C	Tone 1, 2, or 3 (3 different X, K, Ka patterns)	
4th time	TEST YES	D = YES C = NO	X, K, Ka Audio tones 1 beep during Power Up	
5th time	VG2 OFF	D = ON C = OFF	Turns VG-2 On Turns VG-2 Off	
6th time	SR ON	D = ON C = OFF	Turns Safety Radar On Turns Safety Radar Off	
7th time	VOICE OFF	D = ON C = OFF	Real Voice® On Real Voice® Off	

8th time	TEMP	D = YES	Temp On
	NO	C = NO	Temp Off
9th time	BATT NO	D = YES C = NO	Battery Voltage On Battery Voltage Off

\*Factory settings.

Press P/V anytime to exit.

When Custom is displayed, pressing the Quiet button again instead of the P/V button allows changing of other features. If either Dark or City button is pressed it selects one of two preprogrammed selections, night or truck. Once night or truck is selected you cannot change other features in option select mode.

Night = 1. Volume Level 4 2. Auto Quiet On

- 3. Dark Mode
- 4. Highway Mode
- 5. SR On
- 6. VG2 Off
- 7. Test Off
- 8. Voice Off

Truck = 1. Volume level 4

- 2. VG2 On
- 3. Test Off
- 4. Highway Mode
- 5. SR On
- 6. Voice Off

#### Teach/Tutorial Mode

Provides simulated alerts for each type of signal.

Press City and Quiet simultaneously and release. Display reads:

Quiet mode can also be accessed while Teach/Tutorial mode is engaged.

• Press P/V to exit.

#### Voice Module Port

Allows you to use an optional Whistler Voice Module, P/N 202971 (See accessory page for ordering, option mode for programming). Any other device may damage the unit and void your warranty. When mute or auto quiet modes are engaged, the audio will be cancelled to the voice port.

#### Rear Antenna Port

Allows you to use only a Whistler SWRA-3300 rear antenna, P/N 202964. Any other device may damage the unit and void your warranty.

- Remove power from console.
- Plug rear antenna into Radar 2 Port.
- Reapply power to console, after self-test display shows:




• Press Dark to accept or City to cancel.

## **RADAR ALERTS**

#### Speed Radar Audio/Visual Alerts

When X, K or Ka is detected the band ID and signal strength is displayed. The audio alert is continuous and has a geiger counter-like pattern. The faster the beep the closer or stronger the radar source. Example:




An asterisk is displayed when the optional rear antenna receives a signal. Example:



#### Pulse Protection®

When a pulse type signal (instant on strong signal) is detected an urgent 3 second audio warning is sounded and the display reads:




After 3 seconds standard alert pattern continues.

## **SAFETY RADAR ALERTS**

In communities where transmitters are located, the Safety Warning System™ displays over 60 text messages. When Safety Radar is detected the audio alert is geiger counterlike.

# Safety Warning System™ Text Example: Poor Road Surface:



Note: Not all areas have Safety Warning System™ transmitters. Visit Safety Warning System™s web page at www.safetyradar.com for SWS locations.

#### LASER/VG-2 ALERTS

#### Laser Audio/Visual Alerts

When a laser signal is detected the word "Laser" and signal strength is displayed, the audio alert is continuous for a minimum of 3 seconds. Example:



The more "|||" the closer the laser source.

#### VG-2 Audio/Visual Alerts

Note: You must turn this feature on in option select mode before it will detect VG-2.

When a VG-2 signal is detected, the detector "hides" its own radiated signal and becomes undetectable by the VG-2.



Text message confirms detection of VG-2.

Every 30 seconds, the detector checks for a VG-2 signal. If a VG-2 signal is still present, the unit continues to hide and repeats the VG-2 alert. If no signal is detected, two beeps are provided, indicating an "all clear" condition. During VG-2 Alert X, K, and Ka band signals cannot be received. (Reference page 23 for VG-2 information.)

#### **Alert Priority**

When two or more signals are received at the same time, the alert priority is:

- 1. Lasér
- 2. VG-2 3. Speed Radar
- 4. Safety Radar

#### Example:

If X band is alerting, then suddenly VG-2 is detected, the VG-2 warning will override the X band alert.

## **RESET FEATURES/CARE & MAINTENANCE**

#### **Reset Features**

All user features can be reset to factory settings.

- Remove Power from unit.
- Press and hold P/V and Quiet.
- Apply power to the unit.
- · Wait for 2 beeps.
- Release P/V and Quiet. Unit is now reset.
  - 1. Audio to level (4).
  - 2. Display reads Highway.
  - 3. Dim/Dark Mode to full illumination of display.
  - 4. Auto Quiet Mode OFF.
  - 5. VG-2 Detection Mode OFF.
  - 6. Voice OFF.
  - 7. Night Mode OFF.
  - 8. Truck Mode OFF.
  - 9. Safety ON.
  - 10. Full Power Up sequence.
  - 11. Default TONE 3.
  - 12. BATT OFF.
  - 13. TEMP OFF.
  - 14. Rear antenna OFF.
  - 15. Unit ON or OFF.

#### Care And Maintenance

Do not spray water, cleaners or polishes directly onto the unit. The spray may penetrate through the openings and damage the unit. Also, do not use any abrasive cleaners on the unit's exterior.

#### **COMMUNICATION BREAKDOWN**

#### **Communication Breakdown**

If a problem arises between the inside control panel and the outside antennas, the unit will give a unique audio tone. The display reads:







#### If a R1 error occurs:

- Press P/V to turn unit off.
- Check connection in back of control panel (straight ended cable)
- Perform "reset features."
- See dealer/installer.

#### If an R2 error occurs:

- To temporarily cancel error message, momentarily press either Dark/City/Mute button. Next time unit performs self test it will repeat error message.
- To permanently cancel error message, until fixed, press and hold either Dark/City/Mute button.
- If no rear antenna is installed, perform "reset features."
- Press P/V to turn off unit.
- · Check connections in back of control panel.
- · See dealer/installer.

#### If a T error occurs:

- Press P/V to turn off unit.
- Check connection in back of control panel.
- See dealer/installer.

**NOTE**: This T error occurs only at Power Up.

FYI-Laser receiver's cable has a right angled connector.

#### TROUBLESHOOTING GUIDE

Your Whistler detector is expertly engineered and designed to exacting quality standards to provide you with reliable, trouble-free operation. If your unit has been correctly installed following the guidelines in this manual, but is not operating optimally, please refer to the troubleshooting guide below.

#### PROBLEM: No display or audio.

- Check fuse in power cable, replace if necessary.
- Check fuse in fuse box, replace if necessary.
- Make sure power cable is properly grounded.

#### PROBLEM: Unit alarms when vehicle equipment or electrical

- accessories (brakes, power mirrors/windows, directionals, horn, etc.) Check conditions of vehicle's electrical system, including battery
- and alternator. Install a filter capacitor (470 mfd. 25 volt or larger capacitance

#### value) where power connection is made. PROBLEM: Audio alerts are not loud enough.

- Cancel Auto Quiet Mode or City Mode.
- Check audio level setting.

#### PROBLEM: Display shows R1 error. Also see page 19.

- Warning communicates "loss of link" between control panel and rear antenna (RADAR 1).
- Check antenna connection at back of control panel.
- Contact factory, if you suspect antenna is defective.

- PROBLEM: Display shows R2 error. Also see page 19.
  Warning communicates "loss of link" between control panel and rear antenna (RADAR 2); occurs only if rear antenna has been installed.
- Check antenna connection at back of control panel.
- If only one receiver is used-See reset features section to clear this error. Also see page 18.
- Contact factory, if you suspect antenna is defective.

If difficulties occur which cannot be solved by information in this Troubleshooting Guide, please call Whistler Customer Service at 1-800-531-0004 before returning your unit for service.

#### ARE DETECTORS LEGAL?

#### In Most States YES!

Laser detectors are completely legal in every state when used in automobiles or light trucks (under 10,000 lbs.). Similarly, when used in automobiles or light trucks, radar detectors are legal in almost every state. Exceptions are Virginia and Washington, D.C., which have local regulations restricting the use of radar receivers in any vehicle.

Concerning trucks over 10,000 lbs., the Federal Highway Administration (FHWA) issued a regulation, effective January, 1994 which prohibits radar and laser detector use in these types of vehicles nationally.

Prior to the FHWA regulation, laws existed in the state of New York restricting the use of radar detectors in trucks over 18,000 lbs. and in Illinois in trucks over 26,000 lbs.

#### FCC ID HSXWH06

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device many not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### **IMPORTANT**

FCC requirements state that changes or modifications not expressly approved by Whistler could void the user's authority to operate the equipment.

#### **SPEED MONITORING TECHNOLOGIES**

#### Radar Facts

A radar gun operates by transmitting radio waves at certain frequencies which reflect off objects and are then picked up by the radar gun's receiving section. When a radar beam reflects off a moving target, a measurable frequency shift occurs. The radar unit converts this shift into miles per hour to determine your vehicle's speed.

Currently, the FCC (Federal Communications Commission) permits operation of traffic radar guns at X Band (10.500 -10.550 GHz), K Band (24.050 - 24.250 GHz), and Ka Band (33.400 - 36.000 GHz).

#### Laser Facts

It's well documented that many radar guns cannot reliably provide the speed of a targeted vehicle that is traveling in a group of vehicles. In contrast, a laser gun can target a specific vehicle out of a line of traffic and determine its speed. The advantage of laser over radar in terms of target identification is the result of the laser gun's narrow beam. A radar transmission can cover more than a four-lane highway at a distance of 1,000 feet, compared with a laser transmission which covers about 3 feet at the same distance. For best protection, keep these points in mind:

- · Your vehicle's license plate or headlights are the laser gun's
- primary targets.

  Do not follow closely behind any vehicle you cannot see through. If you can't see past a vehicle ahead of you, chances are your detector won't
- The receiving range of your laser detector will not be the same as a radar detector. Laser guns are most often used at short range.

Whistler Laser/Radar detectors receive all current laser guns which operate at a laser wavelength of 905 +/- 10mm.

- Pro Laser<sup>™</sup> I II III
- LT1 20-20
- · Ultra Lyte

#### SPEED MONITORING TECHNOLOGIES

#### Other Speed Detection Systems

Several techniques other than radar or laser are used to measure vehicle speeds. When these methods are being used, no detector can provide a warning. These techniques include:

- Pacing A patrol car drives behind you and matches your driving speed.
- Vascar/Aircraft The time it takes a vehicle to travel a known distance is measured.

#### Radar Detector Detectors (VG-2)

The Interceptor VG-2, or simply VG-2, is a microwave receiver used by police to detect signals radiated by the local oscillator of a radar detector. Because its purpose is to identify persons driving with radar detectors, the VG-2 is known as a "radar detector detector".

The VG-2 is the primary tool used by the police to identify radar detector equipped vehicles. If caught, in a state where detectors are illegal, (see page 21), drivers risk losing their radar detector and receiving a fine. In addition, instant-on radar is almost always used in combination with a VG-2, leaving unsuspecting motorists vulnerable to receiving two tickets — one potentially for speeding, the other for possession of a detector.

NOTE: Having a radar detector capable of detecting the VG-2 may alert you to the presence of a speed trap.

It is the responsibility of the individual radar detector owner to know and understand the laws in your area regarding the legality of the use of radar detectors.

#### WARRANTY INFORMATION

#### **Consumer Warranty**

The 3300A/3400 Whistler detector is warranted to the original purchaser for a period of five years from the date of original purchase against all defects in materials and workmanship. This limited warranty is void if the unit is abused, modified, installed improperly, if the housing and/or serial numbers have been removed. There are no express warranties covering this product other than those set forth in this warranty. All express or implied warranties for this product are limited. Whistler is not liable for damages arising from the use, misuse, or operation of this product. NOTE: This warranty does not include installation or reinstallation charges.

#### Service Under Warranty

During the warranty period, defective units will be repaired without charge to the purchaser when returned with a dated store receipt to the address below. Units returned without dated store receipt will be handled as described in section "Service Out Of Warranty." Due to the specialized equipment necessary for testing a laser/radar receiver, there are no authorized service stations for Whistler brand detectors other than Whistler.

#### WARRANTY INFORMATION

When returning a unit for service under warranty, please follow these instructions:

1. Ship both the console and antenna (CAUTION: DO NOT CUT WIRES when removing the antenna as this will void the warranty.) in the original carton or in a suitable sturdy equivalent, fully insured, with return receipt requested to:

Whistler Repair Dept. 1201 North Dixieland Rd Rogers, AR. 72756

**IMPORTANT:** Whistler will not assume responsibility for loss or damage incurred in shipping. Therefore, please ship your unit insured with return receipt requested.

- 2. Include with your unit the following information, clearly printed:
- Your name and street address (for shipping via UPS), and a daytime telephone number. (No P.O. Box please.)
- A detailed description of the problem (e.g., "Unit per forms self-test but does not respond to radar").
- A copy of your dated proof of purchase or bill of sale.
- Be certain your unit is returned with its serial number. For reference, please write your unit's serial number in the following space:

Antenna s/n
Control Panel s/n
Laser Receiver s/n
standithout corial remains or are not covered under versions

Units without serial numbers are not covered under warranty.

IMPORTANT: To validate that your unit is within the warranty period, make sure you keep a copy of your dated store receipt. You may register your warranty online at www.whistlergroup.com, however, for warranty verification purposes, a copy of your dated store receipt must accompany any unit sent in for warranty work.

#### WARRANTY INFORMATION

#### Service Out Of Warranty

Units will be repaired at "out of warranty" service rates when:

- The unit's original warranty has expired.
- Dated store receipt is not supplied.
- The unit has been returned without its serial number.
- The unit has been abused, modified, installed improperly, or had its housing removed.

The minimum out of warranty service fee for your Whistler detector is \$55.00 (U.S.). If you require out of warranty service, please return your unit as outlined in the section "Service Under Warranty" along with a certified check or money order for \$55.00. Payment may also be made by MasterCard, VISA or American Express; personal checks are not accepted.

In the event repairs cannot be covered by the minimum \$55.00 service fee, you will be contacted by a Whistler technical service specialist who will outline options available to you. If you elect not to have your unit repaired, it will be returned to you and your repair fee refunded. CODs will not be accepted! Therefore, please ship your unit insured with return receipt requested.

**IMPORTANT:** When returning your unit for service, be certain to include a daytime telephone number and email address (if applicable).

#### **Customer Service**

If you have questions concerning the operation of your Whistler detector, or require service during or after the warranty period, please call:

Customer Service
1-800-531-0004
Representatives are available to answer your questions
Monday - Friday
8:00 a.m. to 5:00 p.m (CT).
www.whistlergroup.com

#### **SPECIFICATIONS**

• Dimensions: Antenna: 1.4"H x 3.2"W x 4.2"L

Control Panel: 2.75" L x 2.2" W x 0.75" H

Laser: 1.9" H x .9" W x .6" L

• Weight: Antenna: 7.5 oz.

Control Panel: 2 oz.

#### • Laser Wavelength:

 $905 \pm 50$  nanometers (nm)

#### • Radar Frequencies:

10.500 - 10.550 GHz (X Band) 24.050 - 24.250 GHz (K Band ) 33.400 - 36.000 GHz (Ka Superwideband)

• Operating Temperature Range: -20° C to +80° C (-4° F to +176° F)

#### • Power Requirements:

Operational 12 to 15 volts DC, 200mA nominal

One or more U.S. patents may apply: #5,146,227; #5,379,456; #5,666,120, and #5,990,821.

Specifications are subject to change without notice.

## **ACCESSORIES**

These, and other accessories, can be ordered directly from Whistler by calling 1-800-531-0004 or visit our online store at www.whistlergroup.com.

Order Code	Description	Price	
202971	Voice Module	\$69.95	
202964	Rear Radar Antenna	\$179.95	
	SWRA-3300		
206880	Hardwire Kit (10')	\$9.95	

Shipping and handling (per order) \$5.00

Prices are subject to change without notice.

## **ACCESSORY ORDER FORM**

Name: Street:	SHIP TO:				-
Telepho	ne Number: (	)			
Order C	Code/Description		Quantity	Total	Price
	•		-	\$	
Subt Sales	otal s Tax (if Applicable)				
	ping and Handling			\$5.00	
	Enclosed			\$	
SEVID ODDED EODW WITH CEDTIFIED CHECK					

## SEND ORDER FORM WITH CERTIFIED CHECK OR MONEY ORDER TO:

Whistler CTS PO Box 1844 Bentonville, AR 72712

# IF PAYING BY MASTERCARD, VISA OR AMERICAN EXPRESS PLEASE PROVIDE:

Type of Card \_\_\_MasterCard \_\_\_Visa \_\_\_American Express
Name on Card: \_\_\_\_
Card Number: \_\_\_
Expiration Date: \_\_\_
Cardholder Signature: \_\_\_
\*For expedited shipping costs, contact Whistler Customer
Service, 1-800-531-0004

1-000-331-0004