



How to Use Your Cobra ESD Radar/Laser Detector

Contents

Introduction.....A1
 Safety Alert®/Strobe Alert™
 Federal Law Governing Radar Detectors
 Included Accessories

Controls & Indicators.....A2

Our Thanks to You.....A3
 Customer SupportA3

Features1

Installation2

Quick Start5
 LED Displays.....6

Operation.....9
 Turning On.....9
 Dim Button.....10
 Highway/City Mode.....11
 Muting Mode.....12

Detection.....13
 Band Detection.....13
 Audible Alarm Indicator.....13
 Radar.....14
 VG-2 Undetectable.....14
 Safety Alert/Strobe Alert15
 Radar/VG-2/Laser Alerts.....16
 Facts About Safety Alert®/Strobe Alert™.....17
 Radar Frequencies.....18
 Facts About Lidar (Laser).....19

Maintenance19

Specifications20

Limited One Year Warranty21

Optional Accessories22

Order Form23

If You Think You Need Service.....Back Cover

Features of This Product

- Safety Alert® Traffic Warning System
- Strobe Alert™
- Separate Visual and Audio Alarms
- VG-2 Undetectable
- Auto and Manual Muting
- 3 Level Dim Button
- Superior Audio Volume
- Adjustable Windshield Mounting Bracket

Installation

Installation

Location


Location

Selecting the proper location to mount the Cobra ESD-9000 is very important for optimum performance. Both radar and laser transmissions pass through glass but not through other objects. For this reason the Cobra ESD-9000 lenses must not be blocked. It is best to locate your detector as low on the front windshield as possible.


Examples of metal in the windshield area that can block or weaken incoming radar/laser signals:

1. Windshield wiper blades.
2. Mirrored sun screens.
3. Regular tinted glass does not affect radar reception, although the darker tint at the top of the tinted windshield prevents laser light from penetrating.
4. Heated windshields, currently available as an option for some Ford® (Instaclear) and GM® (Electriclear vehicles act as an impenetrable barrier to radar signals). If in doubt, check with your dealer to see if this applies to your vehicle.


Windshield Mounting




1 Attach cups to bracket.




2 Attach bracket to windshield.




3 Attach detector to bracket.



4 Bend bracket for correct detection angle (if needed). Do not use the ESD-9000 to bend bracket.



5 Plug power cord into detector.



6 Plug power cord into cigarette lighter.

Installation

Quick Start


Dash Mounting

Note


It will be easy for you to remove and reinstall your Cobra ESD-9000 detector at any time using this hook and loop material on the dashboard.

Remember: Without the means to adjust the angle of the detector (when mounted as above), be sure you that your Cobra ESD-9000 has a level, clear view of the road before you attach the hook and loop material.


Dash Mounting




- 1 Peel protective paper off one side of hook and loop material.




- 2 Place on dash.




- 3 Peel top paper off.



- 4 Place detector on hook and loop pad.




- 5 Plug power cord into detector.



- 6 Plug power cord into cigarette lighter.

4

Turn On and Adjust Volume



- 1 Rotate ON-OFF Volume Control to left (away from you). An audible "tone" will indicate the unit is on. PWR LED on front of unit is illuminated.

Turn On and Adjust Volume

5

Quick Start

Set Display Brightness


LED Displays

Note

A three position Dim mode is provided for dusk or night driving (please see Dim Button, page 14 for details).

Set Display Brightness

Select from three levels of LED brightness for your Cobra ESD-9000 display: Normal, Dim and Dark. The ESD-9000's state-of-the-art LEDs present clear alerts even in sunlight.




- 1 Press and release ^{Dim} Dim button to select normal setting. Press and release ^{Dim} Dim button twice to select Dim setting. Press and release Dim button a third time to select Dark setting.


Quick Start

Set Highway/City Mode

City

For urban driving—reduces number of X-Band audible alerts.



- 1 Press and release ^{City} CITY button.
 CITY LED will illuminate orange while in City mode

Highway

For all other driving.

Quick Start


Operation

Set Muting Mode

Set Muting Mode

Auto Muting

Automatically reduces volume of alert in progress after 4 seconds.



Manual Muting

1 Press and release  MUTE button to reduce volume of alert in progress.


To Switch Between Modes

1 Press and release  MUTE Button when no signal is being received.

One "beep" = Mute

Two "beep" = Auto Mute


Turning On Your ESD-9000





1 Plug power cord into detector.



2 Plug power cord into cigarette lighter.



Rotate ON-OFF Volume Control to the left (away from you). An audible "tone" will indicate the unit is on and the  PWR LED on the front of the unit will illuminate orange.



ON mode

Turning On Your ESD-9000

Operation


Dim Button

Dim Button


You may select from three levels of brightness for your Cobra ESD-9000 display: Normal, Dim, and Dark.



- 1 Press and release **DIM** button to reduce the LED display brightness to Dim. A single beep confirms dim led brightness.



- 2 Press and release **DIM** button again to turn LED display off. A single beep confirms no LED display. The power LED will stay on dim.



- 3 Press and release **DIM** button a third time to return led display to Normal. A double beep confirms normal LED brightness.

Note

Normal = "Beep-Beep"
Dim = "Beep"
Dark = "Beep"

Note

The Normal (Bright) mode is automatically engaged when the unit is powered up.


Operation

Highway/City Mode


Highway/City Mode

The Highway/City function is controlled by a 2-step button. The Highway mode is automatically engaged when the unit is powered up. In the City mode, false radar alerts will be reduced.

To engage City Mode:



- 1 Press and release **CITY** button and the **CITY** LED on the front of the unit will illuminate red. A single beep confirms City mode. The X LED will be visible showing you are receiving a signal.



CITY LED will illuminate orange while in CITY mode.

To reactivate the Highway Mode:

- 1 Press and release **CITY** button again. A double beep confirms Highway Mode.

Note

Use City Mode in or near cities where there are many sources of false radar signals such as microwave relay towers and automatic door openers. This will filter out weak signals.

Note

City = "Beep"
Highway = "Beep-Beep"

Operation

Muting Mode


Note


Mute="Beep"
OR
Auto Mute="Beep-Beep"

Muting Mode


The ESD-9000 offers two Mute Modes; Auto and Manual. To switch between these modes:

Auto Mode



1 Press and release  MUTE button when no signal is being received. In Auto mode, the alarm will be reduced in volume after three seconds. AutoMute mode is automatically engaged when the unit is powered up.

Manual Mode



1 Press and release  MUTE button to turn off the audio when an alarm is in progress

Detection

Band Detection


Band Detection

This detector is designed to detect X, K, Superwide Ka Band Radar, Laser (including LTI 20-20, Ultra Lyte and ProLaser technologies), VG-2, Safety Alert and Strobe Alert signals.

Audible Alarm Speaker

Audible Alarm Speaker

A different alert tone will sound for X, K, Ka, Laser (plus a distinctly different tone for each of the three laser signals: LTI 20-20, Ultra Lyte and ProLaser), VG-2, and Safety/Strobe Alert signals.




Detection

Radar

Radar

The display will show the band (X,K/Ka).The signal strength will first be indicated by the band being illuminated, then the band plus -, finally the band plus - and = will be illuminated. At the same time the frequency of the beeps will increase.



Instant-On Detection

The Cobra ESD-9000 is also designed to detect Instant-on speed monitoring signals. **Immediate action is required when warning is given.**

VG-2 Alert

Note

The display does not indicate signal strength.

VG-2 Undetectable

The Cobra ESD 9000 is undetectable by police VG-2 detection devices. It will alert you when one is in use near your vehicle. During this time, the unit is still on full alert and able to detect other signals.




The V VG-2 LED on the front of the unit will illuminate yellow.

Detection

Safety Alert® Traffic Warning System and Strobe Alert™

Safety Alert® Traffic Warning System and Strobe Alert™

Indicator "W" is illuminated.




Laser

Note

The display does not indicate signal strength.

Laser

Laser will trigger 3 distinct audible signals;one each for LTI 20-20,Ultra Lyte and ProLaser.



Detection

Radar/VG-2/ Laser Alerts

Radar/VG-2/Laser Alerts

Type of Audible Signal	Interpretation and Response
Your COBRA ESD-9000 starts to signal slowly, then increases in rate very rapidly.	Most likely police radar. FULL ALERT.
Your COBRA ESD-9000 signals just once.	Most likely a false source, or could be pulsed radar. Exercise Caution.
Very fast signal rate instantly.	Radar or VG-2 close by has been suddenly switched on. FULL ALERT.
Slow signal rate as you approach hill or bridge. Sharp increase in signal rate as you reach hill or bridge.	Most likely police radar on other side of hill or bridge. FULL ALERT.
Short-term, weak signaling; series of such signals.	Most likely a false radar source. Exercise Caution.
Laser will trigger 3 distinct audible signals; one each for LTI 20-20, Ultra Lyte and ProLaser.	Use Full Caution. There are no false laser signals.
Safety Alert and Strobe Alert have their own unique "European Emergency" signal.	An emergency vehicle is approaching, you are in the vicinity of a railroad crossing, or you are approaching a road hazard (construction site, accident scene, etc.).

Detection

Facts About Safety Alert® Traffic Warning System

Facts About the Safety Alert® Traffic Warning System

FCC-approved Safety Alert Transmitters emit microwave radar signals to indicate the presence of a safety-related concern. Depending on the frequency of these signals, as set on the transmitter, the outgoing signal can indicate whether the transmitter is on a speeding emergency vehicle or train, or at a stationary road hazard location. These microwave signals are located in the K-band and as a result, any radar detector which detects K-band radar will detect these Safety signals as standard K-band radar alerts. However, unlike a standard radar detector, your Cobra ESD-9000 is designed to differentiate between a standard K-band alert and a Safety Alert warning.

Safety technology is relatively new so the number of transmitters in operation is still growing. You may not receive Safety Alert on a daily basis and should not be surprised to encounter some emergency vehicles, road hazards or trains not yet equipped with these transmitters, therefore failing to provide a signal. As Safety Transmitters become more prevalent (the number of operating transmitters is growing every day), these Safety Alerts will become more common. The Safety Alert Transmitter is in use in all 50 states in limited quantities.

Facts About Strobe Alert™

Alerts motorists to over 50,000 emergency vehicles equipped with strobe transmitters that activate red lights at traffic intersections in emergency high speed situations.

Note

Strobe Alert™ is available in over 1,000 cities and works with Tomar and Opticom systems. Call your local Fire/Police department for your area coverage or area in which you will be traveling.

Detection

Detection

Radar Frequencies

Radar Frequencies

There are now three frequencies that have been approved by the FCC (Federal Communications Commission) for use in speed monitoring equipment. They are:

- X Band (10.525 GHz),K Band (24.150 GHz)
- Ka Band (33.400-36.000 GHz)

Your Cobra ESD-9000 can detect signals in all three radar bands including photo radar and STALKER radar which use the Ka band, and Cobra's Safety Alert signals on the K band.

Facts About LIDAR (Laser)

LIDARs must have a clear line of sight to target a vehicle during the entire measurement interval. Intervening objects such as signposts, utility poles, tree branches, etc., will prevent a valid speed reading.


Facts About LIDAR (Laser)

What is LIDAR?

LIDAR stands for Light Detection And Ranging. While everyone refers to it as LASER the correct name is LIDAR.

How does LIDAR work?

LIDAR operates a lot like RADAR. Like RADAR, it spreads out. Not as quickly, but it does spread, as shown on the diagram below.



Does weather have any effect on LIDAR?

Yes, rain, snow, smoke, fog, and airborne dust particles will all reduce the effective range, and if sufficiently dense, may prevent its operation.

Can LIDAR operate through glass?

No, LIDAR guns cannot obtain readings through any glass. But the laser pulse can be received through glass to easily and quickly trigger a laser detector's alarm.

Can LIDAR operate while moving?

No, since LIDAR is line of sight, an officer cannot drive, aim, and shoot while driving.

Is a LIDAR DETECTOR legal to use?

Yes, it is legal in all 50 states.

Maintenance

Your COBRA ESD-9000 RADAR/LASER DETECTOR will give you years of trouble-free service with minimum maintenance.

Replacing Power Cord Fuse

Unscrew cap of cigarette lighter adapter and remove fuse. Replace with 1-ampere fuse only.

Troubleshooting

If your COBRA LASER DETECTOR ESD-9000 isn't operating, we suggest you make the following checks:

1. Is the power cord properly connected?
2. Is the fuse OK?
3. Is the cigarette lighter socket clean and free from corrosion?

Facts About LIDAR (Laser)

Maintenance

Specifications



Limited One Year Warranty

Specifications

GENERAL SPECIFICATIONS

A. FREQUENCIES

- | | |
|---------------------|-------------------------|
| 1. X BAND | 10.525 GHz ± 50 MHz |
| 2. K BAND | 24.150 GHz ± 100 MHz |
| 3. Ka BAND | 33.4 - 36.0 GHz |
| 4. VG-2 | 11.4 GHz - 11.7 GHz |
| 5. Safety Alert | 24.07, 24.11, 24.19 GHz |
| 6. LTI 20-20 Laser | 300 THz - 375 THz |
| 7. Strobe Alert | 300 THz - 770 THz |
| 8. Ultra Lyte Laser | 300 THz - 375 THz |
| 9. ProLaser | 300 THz - 375 THz |

B. UNIT DIMENSIONS

3-3/16"W x 1-1/4"H x 5"D

COBRA ELECTRONICS CORPORATION warrants that its COBRA 9 Band Radar/Laser Detectors, and the component parts thereof, will be free of defects in workmanship and materials for period of one (1) year from the date of first consumer purchase. This warranty may be enforced by the first consumer purchaser, provided that the product is utilized within the U.S.A.

COBRA will, without charge, repair or replace, at its option, defective 9 Band Radar/Laser Detectors, products or component parts upon delivery to the COBRA factory Service Department, accompanied by proof of the date of first consumer purchase, such as a duplicated copy of a sales receipt.

You must pay any initial shipping charges required to ship the product for warranty service, but the return charges will be at Cobra's expense, if the product is repaired or replaced under warranty.

Exclusions: This limited warranty does not apply; 1) to any product damaged by accident; 2) in the event of misuse or abuse of the product or as a result of unauthorized alterations or repairs; 3) if the serial number has been altered, defaced or removed; 4) if the owner of the product resides outside the U.S.A.

All implied warranties, including warranties of merchantability and fitness for a particular purpose are limited in duration to the length of this warranty.

COBRA shall not be liable for any incidental, consequential or other damages; including, without limitation, damages resulting from loss of use or cost of installation.

Some states do not allow limitations on how long an implied warranty lasts and/or do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.



Cobra Electronics Corporation


6500 West Cortland Street
Chicago, Illinois 60707
www.cobraelec.com

Optional Accessories

Accessory Order Form



Straight 12V DC Power Cord
Includes plug and fuse
420-080-N-001 \$10.00



Curled 12V DC Power Cord
Includes plug and fuse
420-080-N-002 \$10.00



Windshield Mounting Bracket
Includes suction cups
545-139-N-001 \$7.00

Item #	Description	Cost Ea.	Qty.	Amount
420-080-N-001	Straight 12V Power Cord	\$10.00		
420-080-N-002	Curled 12V Power Cord	\$10.00		
545-139-N-001	Windshield Mounting Bracket	\$7.00		

Prices subject to change without notice.

Tax Table
Illinois residents add 7%
Cook Co. residents add .75% (7.75% total)
Chicago residents add 1% (8.75% total)
Indiana residents add 5%
Michigan residents add 4%
Minnesota residents add 6%
Ohio residents add 6%
Wisconsin residents add 5%

Subtotal _____
(Tax if applicable) _____
Shipping/handling \$4.00
Total _____

For credit card orders fill out order form
and fax to: 1.773.622.2269
or call 1.773.889.3087
(Press 1 from the main menu)
8:00 am - 8:00 pm, M-F, CST.

Make check or money order (no stamps)
payable to:
Cobra Electronics
6500 West Cortland St.
Chicago, IL 60707
Attn: Accessories Dept.

Please print clearly

Name _____

Address (No P.O. Box) _____

City _____ State _____

Zip _____

Telephone (____) _____

Credit Card No. _____ Exp. Date _____

Customer Signature _____

Circle One: Visa MasterCard Discover

Allow 4 to 6 weeks for delivery. Offer valid in Continental U.S. only.

You Can Find These Fine Accessories At Your Local Cobra Dealer


If you wish, you can order directly from Cobra.

Order by phone

Call 1.773.889.3087 (Press 1 from the main menu)
8 a.m.-8 p.m. M-F CST.)

Order by mail or fax


Please fill out order form on next page, and mail/fax directly to Cobra.



**The Cobra line of quality products
also includes:**

- **CB Radios**
- **MicroTalk™ Radios**
- **Accessories**
- **SafetyAlert™
Traffic Warning Systems**

Nothing comes close to a Cobra™



Introduction

© 1999 Cobra Electronics Corporation
6500 West Cortland Street
Chicago, IL 60707
www.cobraelec.com

If You Think You Need Service

For technical assistance, please call our Automated Help Desk which can assist you by answering the most frequently asked questions about Cobra products.

(773) 889-3087

24 hours a day, 7 days a week.

A Consumer Service Representative can be reached through this same number 8:00 am - 8:00 pm, Monday through Friday, CST.

Technical assistance is also available on-line in the Frequently Asked Questions (FAQ) section at www.cobraelec.com or by e-mail to productinfo@cobraelec.com

If you think you need service call 1.773.889.3087

"If your product should require factory service please call Cobra first before sending your unit in. This will ensure the fastest turn-around time on your repair."

You may be asked to send your unit to the Cobra factory. It will be necessary to furnish the following in order to have the product serviced and returned.

1. For Warranty Repair include some form of proof-of-purchase, such as a mechanical reproduction or carbon or a sales receipt. If you send the original receipt it cannot be returned.
2. Send the entire product.
3. Enclose a description of what is happening with the unit. Include a typed or clearly print name and address of where the unit is to be returned.
4. Pack unit securely to prevent damage in transit. If possible, use the original packing material.
5. Ship prepaid and insured by way of a traceable carrier such as United Parcel Service (UPS) or First Class Mail to: Cobra Factory Service, Cobra Electronics Corporation, 6500 W. Cortland St., Chicago, IL 60707.
6. If the unit is in warranty, upon receipt of your unit it will either be repaired or exchanged depending on the model. Please allow approximately 3 to 4 weeks before contacting us for status. If the unit is out of warranty a letter will automatically be sent informing you of the repair charge or replacement charge. If you have any questions, please call 1.773.889.3087 for assistance.


© 1999 Cobra Electronics Corp.
Printed in Thailand

Part No. 480-296-P-001

Operating Instructions for your Cobra 9 Band Extra Sensory Detection Radar/Laser Detector Model ESD-9000




Nothing comes close to a Cobra™



and Strobe Alert™

Use of this product is not intended to, and does not, ensure that the motorist and any passenger will not be involved in a traffic accident. It is only intended to alert the motorist that an emergency or service vehicle equipped with a CODE 3, Strobe (Opticom or Tomar Preemption System) or Cobra Safety Alert Transmitter is in the area as defined by the range of the product. Please call your local Fire/Police department to verify if coverage exists in your area. Motorists are expected to exercise all due caution while using this product, and to observe and follow all applicable traffic laws. Operators of emergency or service vehicles are also expected to exercise all due caution while using this product, and to observe and follow all applicable traffic laws.*

*Opticom is a registered trademark of 3M Corporation



Introduction

Congratulations! You have just purchased the most sophisticated RADAR/LASER DETECTOR available today. This booklet contains instructions and information designed so that you will be able to understand how the Cobra ESD™-9000 works and how radar and (LIDAR) laser are used. Enjoy your Cobra ESD-9000 Radar/Laser Detector and **drive safely.**

Federal Law Governing Use of Radar Detectors

It is not against Federal Law to receive radar transmissions on your COBRA Radar Detector. The Communications Act of 1934 guarantees your right to receive radio transmissions on any frequency. Local laws that contravene the Communications Act of 1934, while illegal, may be enforced by your local law enforcement officials until and unless they are prohibited from doing so by Federal Court action.

WARNING: Before leaving your car, make sure that you conceal your radar detector. This will reduce the possibility of break-in and theft of your unit.


Included with your ESD-9000

1. Windshield Bracket
2. Hook and Loop Material
3. Power Cord

A1

Controls and Indicators

1. On/Off Volume Control
2. Mute Button
3. Dim Button
4. Audio Alerts Speaker
5. Highway/City Button
6. Band Indicators
7. Signal Strength LEDs
8. Windshield Bracket Mount
9. 12V DC Power Jack



Thank you for purchasing the Cobra ESD-9000 Radar/Laser Detector. Properly used, this Cobra product will give you many years of reliable service.

Customer Support

Should you encounter any problems with the product or not understand its many features, please refer to this owner's manual. If, after referring to the manual, you still need help, call Cobra Customer Service at 773.889.3087.

Cobra Customer Service

Live operators are available
M-F 8:00 am - 8:00 pm CST
at: 773.889.3087

Automated Technical
Assistance available 24 hours
a day, seven days a week.
E-mail questions to:
productinfo@cobraelec.com

Cobra on the World Wide Web:
Frequently Asked Questions
(FAQ) can be found on-line
at: www.cobraelec.com